MS305 SMALL STOCK STUNNER



Jarvis Manual Sheep Stunning Control cabinet for the Electrical stunning of Sheep, for both Halal and Full Kill Stunning

- Safe Stunning voltage isolated for operator safety with two handed anti tie down triggers
- Adjustable Current 6 settings 0.7 – 2.0 Amps
- Multiple Species Setting 3 settings Stun time and stun fail criteria adjustable for different species
- Humane Current sensing electronics monitor each stun, with warning light for Stun Fail
- Short Circuit Proof Current limiting Choke short circuit proofs the output probes
- Certified Components Fully complies with AS.3108 and NZS6116



Jarvis Engineering Technologies



SUPERIOR STUN QUALITY

Specifications

Capacity Controls Overall dimensions

Shipping Dimensions Weight Up to 600/Hr Two handed with anti-tie down control Cabinet 400 mm H x 400 mm W x 200 D (Includes Meter Cabinet) 1000mm x 500mm x 450mm Cabinet = 55KG Shipping = 65 KG

Electrical Specifications

Supply Voltage Output Voltage Output Current Current Selection Stun Time 230V AC 50 / 60 Hz 550VAC 0.7 – 2.0 Amps 6 Position Switch 0 – 6sec (Adjustable)

Equipment Selection

MS105 M1J Handset M1C Handset	Cabinet c/w Safety Push Button Model 1J Handset for Head Only Stunning Model 1C 'Pneumatic Clamp' Handset for head only stunning	3863030 7150400J 7150415J
Balancer	Spring Balancer for M1J Handset	7150650
M2 Handset	Model 2 Handset for Head to Back Stunning	7150410J
Balancer	Spring Balancer for M2J Handset	7150651
Meter Box	Meter box c/w Voltmeter, ammeter and indicator lamps	3863008
Solenoid Kit	Water solenoid assembly	3822009
Valve Plate	Pneumatic and water valve assembly for M1C Handset	3822005



Products for the Meat and Poultry Industry