

# CIRCULAR BREAKING SAW

## Model SEC 230-4, SEC 230-4LN



**The Jarvis Model SEC 230-4 - electrically powered circular breaking saw.**

# JARVIS

- The SEC 230-4, with a 3 inch (76 mm) depth of cut, is ideally suited for:
  - Beef: cutting chucks, shoulders, ribs, forequarters, hindquarters, chine bones, briskets and loins.
- Sealed, 2.25 hp electric motor for ultimate performance.
- Short overall length and specially designed handles for easy handling.
- Features electric or mechanical braking.
- Smooth surface construction for easy cleaning and optimum hygiene.
- Anti-tie down controls for operator safety.
- Meets national and international requirements for hygiene and safety.



**SMOOTH - POWERFUL - RUGGED**

# CIRCULAR BREAKING SAW

## Model SEC 230-4, SEC 230-4LN

### Specifications

Drive	Electric	
<b>Model SEC 230-4, SEC 230-4LN</b>		
Motor Power	2.25 hp	1700 W
Operating Voltage	415 / 400 / 230 / 115 / 42 V, 3 phase, 50 Hz	
Blade Speed	575 / 480 / 380 / 240 / 208 V, 3 phase, 60 Hz	
50 Hz		1350 rpm
60 Hz		1650 rpm
Control Handle	Electric Dual Anti-tie Down or One Trigger (CE)	
Brake	Electric (DC) or Mechanical	
Blade Diameter	9.1 in	230 mm
Cutting Depth (maximum)	3.0 in	76 mm
Overall Length	24 in	610 mm
Weight	40 lbs	18.1 kg
Vibration	less than 108 dB	<0.25 m / sec <sup>2</sup>
Noise (one meter from tool)		less than 80 dB

### Equipment Selection and Accessories

### Order Number

Model Sec 230-4		
42 V, 3 phase, 50 Hz with DC brake		4004218
42 V, 3 phase, 50 Hz with mechanical brake		4004206
115 V, 3 phase, 50 Hz with mechanical brake		4004246
230 V, 3 phase, 50 Hz with mechanical brake		4004207
240 V, 3 phase, 60 Hz with mechanical brake		4004215
240 V, 3 phase, 60 Hz with DC brake		4004217
380 V, 3 phase, 50 Hz with mechanical brake		4004205
480 V, 3 phase, 60 Hz with DC brake		4004216
480 V, 3 phase, 60 Hz with mechanical brake		4004214
Model Sec 230-4LN		
42 V, 3 phase, 50 Hz with DC brake		4004221
42 V, 3 phase, 50 Hz with mechanical brake		4004224
240 V, 3 phase, 60 Hz with DC brake		4004220
240 V, 3 phase, 60 Hz with mechanical brake		4004223
480 V, 3 phase, 60 Hz with DC brake		4004219
480 V, 3 phase, 60 Hz with mechanical brake		4004222
Blades	<i>Please specify blade preference when ordering.</i>	
9.1 in / 230 mm diameter - 130 teeth		1023286
9.1 in / 230 mm diameter, Skip Tooth - 72 teeth		1023387
9.1 in / 230 mm diameter, Noise Reduction - random skip tooth		1023299
9.1 in / 230 mm diameter, Noise Reduction - 60 teeth		1023348
Balancer		4042035



Products for the meat and poultry industry